

## Circulator bath Metos Fusion Diamond M 230V1~

Circulator is mounted on a bridge over the bath. VFD -display, resolution  $\pm$  0.01  $^{\circ}$ C

- safety protection grid prevents the vacuum pouch from touching moving and heated parts.
- circulating pump ensures optimal temperature stability and water distribution throughout the bath
- 3 integrated timers allows for easy monitoring of the elapsed or remaining cooking time.
- pre-programmed memory keys for 3 different types of foods
- easy HACCP data logging
- Smudge-Proof Stainless Steel Hood
- Low-Level Water Alarm
- Vapor Barrier Protection
- Core Temperature Detection (audible and visual)
- Intuitive Automatic Calibration
- Simultaneous Display of Setpoint, Current Temperature, Core Temperature/Timer
- PC Controlled Accessories (will be charged separately)
- separation grids
- core temp sensor Pt100
- sous-vide neopreeni -tape
- HACCP software
- PC -cables, USB or RS232





## Circulator bath Metos Fusion Diamond M 230V1~

n width mm 332 n depth mm 577 n height mm 424 ckage volume 0.001	
n height mm 424	
skage volume	
kage volume 0.00 i	m3
t of volume m3	m3
ckage volume 0.001	
ckage length 67.7	
ckage width 52.4	
ckage height 43.2	
ckage unit of dimension cm	
ckage dimensions (LxWxH) 67.7x	52.4x43.2 cm
weight 15	
weight 15 kg	
ess weight 17	
ckage weight 17 kg	
t of weight kg	
nnection power kW 2	
se Size A	
nnection voltage V 230	
mber of phases 1N	
quency Hz 50	
e of electrical connection Plug	
ctrical conn. height mm 200	
marks (electrical)	