

Food transport trolley

Metos Thermobox EE150

The Metos Thermobox EE150 food transport trolley is an efficient solution for heat storage and transportation of warm food. The trolley has two cabinets stacked on top of each other. The trolley's patented membrane resistance heating and precise electronic temperature control ensure safe and high-quality conditions for storage and transportation of warm food. The E-trolley keeps the temperature at the desired level with minimal temperature fluctuations. The temperature control unit is located at the top of the trolley and has a large digital temperature display.

The trolley is insulated with polyurethane, which expands under high pressure and unites the trolley's construction and the inner chambers into a strong and well-insulated unit. The trolley's energy-efficient insulation ensures safe and high-quality conditions for storage and transport of food.

The trolley can be used in small spaces. The trolley is easy to clean as its inside is completely made of stainless steel and has pressed GN guides without any joints. Large rubber wheels as well as bumpers and ergonomic handles around the stroller make the stroller easy to handle and light. The robust door can be opened comfortably by pulling the handle, which is integrated in the frame. The door opens to the side, 270 degrees.

- the capacity is 4xGN1/1, inner dimension: 330x540x350 mm + 6xGN1/1, inner dimensions: 330x540x510 mm, guide distance 80 mm
- temperature range: +40°C...+90°C
- smaller cabinet on top of the bigger cabinet
- four hot-dip galvanized steel 160mm wheels with



- rubber tires, two swiveling with brakes and two fixed without brakes
- the wheel bracket is made of hot-dip galvanized steel
 - the exterior of the red trolley is made of ABS plastic
 - stainless steel handle and PVC plastic corner
 - the bumper is made of galvanized steel and coated with PVC plastic
 - Shuko connector connection, 1,5-2 m spiral cord and holder for plug

Accessories(charged separately):

- truck tow bar
- door with window
- two extra handles
- address card holders A4, A5, A6
- Ø200 mm wheels, two directionally locked and two with brake
- terrain wheels
- blue or black color without extra price, own color, image or logo for extra price
- central brake rubber tires, two swiveling with brakes and two fixed without brakes
- the wheel bracket is made of hot-dip galvanized steel
- the exterior of the red trolley is made of ABS plastic
- stainless steel handle and PVC plastic corner
- the bumper is made of galvanized steel and coated with PVC plastic
- Shuko connector connection, 1,5-2 m spiral cord and holder for plug

Accessories(charged separately):

- truck tow bar
- door with window
- two extra handles
- address card holders A4, A5, A6
- Ø200 mm wheels, two directionally locked and two with brake
- terrain wheels
- blue or black color without extra price, own color, image or logo for extra price
- central brake

Food transport trolley Metos Thermobox EE150

| | |
|-------------------------------|------------------------------|
| Product capacity | 4+6 x GN 1/1-65 |
| Capacity | 10 x GN 1/1-65 |
| Inside measures mm | 330x540x510+350 |
| Item width mm | 525 |
| Item depth mm | 710 |
| Item height mm | 1285 |
| Package volume | 0.583 |
| Unit of volume | m3 |
| Package volume | 0.583 m3 |
| Package length | 58 |
| Package width | 75 |
| Package height | 134 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 58x75x134 cm |
| Net weight | 56 |
| Net weight | 56 kg |
| Gross weight | 57 |
| Package weight | 57 kg |
| Unit of weight | kg |
| Connection power kW | 0.78 |
| Connection voltage V | 230 |
| Number of phases | 1NPE |
| Frequency Hz | 50 |
| Protection rating (IP) | 55 |
| Electrical cable length mm | 1500 |
| Type of electrical connection | Plug |
| Remarks (electrical) | connection power 0,5+0,28 kW |
| Hinge location | right |
| Cleaning | hand wash |

Food transport trolley Metos Thermobox EE150

| | |
|---------------------|--------------------------|
| Function | warm |
| GN size | 1/1 |
| Temperature area °C | +40°C...+90°C |
| Features | 30 kg per pair of guides |
| Rail distance mm | 80 |
| Number of chambers | 2 |
| Power range kW | 0.95 |
| Max load kg | 90 |
| Color | red |