

## Chilled display Metos Green OE-80-89-E-R290

Metos Green OE-80-89-E is a recessed, self-serve chilled display designed for use under demanding conditions, with a width of 800 mm and height of 890 mm. The simple squared shape of the chilled display highlights the products being sold.

The display's tempered glass side panels, the glass shelf and the bright LED lighting for shelves and the cold tub make products being sold highly visible. The self-service display is open on the customer side, with hinged glass doors on the seller's side. A 215 mm high cooled tub with Gastronorm dimensioning.

In addition, the display is equipped with an auto-defrost function, the melting water from which is directed to the grey water system. For those installation locations where it is not possible to connect the display to the grey water system, an condensate evaporation tank is included as an accessory.

The display is equipped with air cooled chilling, digital temperature control and a fan speed regulator. Air temperature range is +2...+4 °C. The glass side panels and glass shelf is made from tempered glass. The substructure is made from stainless steel and insulation is polyurethane.

- recessable into furniture (cut out size 740 x 670 m)
- shelf and tub lighting
- tempered glass side panels and shelf
- sales space 0.74 m<sup>2</sup>
- temperature area +2...+4 °C
- digital temperature regulation
- ventilator speed regulator
- easy to clean

EXTRA ACCESSORIES (can be ordered separately):

- sneeze guard for shelf
- price tag frame;
- evaporation



tank; Manual or Electrical 1000W tank; Manual or Electrical 1000W

## Chilled display Metos Green OE-80-89-E-R290

Product capacity	2x GN1/1+3 shelves
Item width mm	800
Item depth mm	695
Item height mm	890/1565
Package volume	1.925
Unit of volume	m3
Package volume	1.925 m3
Package length	110
Package width	100
Package height	175
Package unit of dimension	cm
Package dimensions (LxWxH)	110x100x175 cm
Net weight	175
Net weight	175 kg
Gross weight	195
Package weight	195 kg
Unit of weight	kg
Connection power kW	0.844
Fuse Size A	10
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50
Drain diameter	30
Cooling capacity W	1570
Type of the refrigerant	R290
Sound level dB	70
Energy class rating	F