

Prerinse machine curv. R-L

Metos WD PRM90

The Metos PRM90 prerinse machine is economical to use. It utilizes the exit water from the basket conveyor machine by recycling it in the pre-washer. When selecting water intake from the washing machine, the fresh water consumption is only 30 liters that fills the tank. The machine is placed clearly apart from the dishwasher so that the pre-wash water cannot mix with the washing machine water. The pre-rinse machine has a unit-wide door that can be opened from the front, which makes cleaning easier.

- including rinsing shower



Prerinse machine curv. R-L Metos WD PRM90

Item width mm	950
Item depth mm	950
Item height mm	1400/1920
Package volume	1.618
Unit of volume	m3
Package volume	1.618 m3
Package length	97
Package width	97
Package height	172
Package unit of dimension	cm
Package dimensions (LxWxH)	97x97x172 cm
Net weight	175
Net weight	175 kg
Gross weight	205
Package weight	205 kg
Unit of weight	kg
Connection power kW	0.8
Fuse Size A	10
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Type of electrical connection	Semifixed
Electrical conn. height mm	172
Cold water diam.	R"1/2"
Cold water flow l/min	11
Cold water min pressure kPa	250
Cold water max pressure kPa	600
Cold water conn. height mm	172
Hot water conn. height mm	1395

Prerinse machine curv. R-L Metos WD PRM90

Drain diameter	50
Drain flow l/s	3
Drain conn. inlet	Right;Behind;Bottom
Drain conn. height mm	163
Floor drain needed	Yes
Sound level dB	68
Ventilation machine m ³ /h	200